



CODE	BUBBLE TUBING [®]	DIMENSIONS			
		TUBING I.D. A	TUBING O.D. B	BALLAST O.D. C	WIRE CABLE [*] D
BUB12NW	1/2 (15MM) NON-WEIGHTED	0.575" (14.6 MM)	0.700" (17.8 MM)		
BUB12	1/2 (15MM) WEIGHTED	0.575" (14.6 MM)	0.700" (17.8 MM)	0.970" (24.6 MM)	
BUB34NW	3/4 (20MM) NON-WEIGHTED	0.825" (21 MM)	1.013" (25.7 MM)		
BUB34	3/4 (20MM) WEIGHTED	0.825" (21 MM)	1.013" (25.7 MM)	1.170" (29.7 MM)	1/4" (6.4 MM)
BUB1.0	1" (25MM) WEIGHTED	1.075" (27.3 MM)	1.2" (30.5 MM)	1.550" (39.4 MM)	1/4" (6.4 MM)
BUB1.25	1-1/4 (30MM)	1.325" (33.7 MM)	1.513" (38.4 MM)	1.550" (39.4 MM)	1/4" (6.4 MM)

*7-19 STRAND CORE (SS-316)

CODE	BUBBLE TUBING [®]	PRESSURE		WEIGHT
		MIN.	MAX.**	
BUB12NW	1/2 (15MM) NON-WEIGHTED	20 PSI (1.4 BAR)	50 PSI (3.4 BAR)	0.1 lb/ft (0.15 kg/m)
BUB12	1/2 (15MM) WEIGHTED	20 PSI (1.4 BAR)	50 PSI (3.4 BAR)	0.6 lb/ft (0.9 kg/m)
BUB34NW	3/4 (20MM) NON-WEIGHTED	20 PSI (1.4 BAR)	70 PSI (4.8 BAR)	0.2 lb/ft (0.30 kg/m)
BUB34	3/4 (20MM) WEIGHTED	20 PSI (1.4 BAR)	70 PSI (4.8 BAR)	1.0 lb/ft (1.5 kg/m)
BUB1.0	1" (25MM) WEIGHTED	20 PSI (1.4 BAR)	70 PSI (4.8 BAR)	1.65 lb/ft (2.45 kg/m)
BUB1.25	1-1/4 (30MM)	20 PSI (1.4 BAR)	70 PSI (4.8 BAR)	1.70 lb/ft (2.52 kg/m)

**MAXIMUM BACK PRESSURE READING NOT TO EXCEED DURING OPERATION

TOUTE INFORMATION CONTENUE DANS CE DOCUMENT EST LA PROPRIÉTÉ EXCLUSIVE DE PRODUITS ETANG.CA LTÉE. TOUTE REPRODUCTION PARTIELLE OU ENTIÈRE EST STRICTEMENT INTERDITE SANS AU PRÉALABLE AVOIR REÇU L'AUTORISATION ÉCRITE DE PRODUITS ETANG.CA LTÉE.
 ALL INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO CANADIAN POND.CA PRODUCTS LTD. DUPLICATION OR TRANSMITTAL OF THIS DOCUMENT IS STRICTLY PROHIBITED WITHOUT THE WRITTEN CONSENT OF CANADIANPOND.CA PRODUCTS LTD.

Canadiampond.ca
Etang.ca

DESIGNÉ PAR / DRAWN BY: D. MARTIN
 APPROUVÉ PAR / APPROVED BY: M. PARSIS

DATE: 28-06-2017

513 KNOWLTON ROAD, KNOWLTON, QUÉBEC, JOE 1W0. TEL: 450-243-0976. FAX: 450-243-1834

TITRE / TITLE:

