



DIMENSIONS					
CODE	TUYAU-BULLE®	D.I. TUBE	D.E. TUBE	D.E. BALLAST	CÂBLE D'ACIER*
		A	B	C	D
BUB12NW	1/2 (15MM) NON-LESTÉ	0.575" (14.6 MM)	0.700" (17.8 MM)		
BUB12	1/2 (15MM) LESTÉ	0.575" (14.6 MM)	0.700" (17.8 MM)	0.970" (24.6 MM)	
BUB34NW	3/4 (20MM) NON-LESTÉ	0.825" (21 MM)	1.013" (25.7 MM)		
BUB34	3/4 (20MM) LESTÉ	0.825" (21 MM)	1.013" (25.7 MM)	1.170" (29.7 MM)	1/4" (6.4 MM)
BUB1.0	1" (25MM) LESTÉ	1.075" (27.3 MM)	1.2" (30.5 MM)	1.550" (39.4 MM)	1/4" (6.4 MM)
BUB1.25	1-1/4 (30MM)	1.325" (33.7 MM)	1.513" (38.4 MM)	1.550" (39.4 MM)	1/4" (6.4 MM)

*7-19 TORON TRESSÉ (INOX.316)

PARAMÈTRES				
CODE	TUYAU-BULLE®	PRESSION		POIDS
		MIN.	MAX.**	
BUB12NW	1/2 (15MM) NON-LESTÉ	20 PSI (1.4 BAR)	50 PSI (3.4 BAR)	0.1 lb/ft (0.15 kg/m)
BUB12	1/2 (15MM) LESTÉ	20 PSI (1.4 BAR)	50 PSI (3.4 BAR)	0.6 lb/ft (0.9 kg/m)
BUB34NW	3/4 (20MM) NON-LESTÉ	20 PSI (1.4 BAR)	70 PSI (4.8 BAR)	0.2 lb/ft (0.30 kg/m)
BUB34	3/4 (20MM) LESTÉ	20 PSI (1.4 BAR)	70 PSI (4.8 BAR)	1.0 lb/ft (1.5 kg/m)
BUB1.0	1" (25MM) LESTÉ	20 PSI (1.4 BAR)	70 PSI (4.8 BAR)	1.65 lb/ft (2.45 kg/m)
BUB1.25	1-1/4 (30MM)	20 PSI (1.4 BAR)	70 PSI (4.8 BAR)	1.70 lb/ft (2.52 kg/m)

**LECTURE MAXIMALE DE RETOUR DE PRESSION À NE PAS DÉPASSER DURANT L'OPÉRATION

TOUTE INFORMATION CONTENUE DANS CE DOCUMENT EST LA PROPRIÉTÉ EXCLUSIVE DE PRODUITS ETANG.CA LTÉE. TOUTE REPRODUCTION PARTIELLE OU ENTIÈRE EST STRICTEMENT INTERDITE SANS AU PRÉALABLE AVOIR REÇU L'AUTORISATION ÉCRITE DE PRODUITS ETANG.CA LTÉE.

ALL INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO CANADIAN POND.CA PRODUCTS LTD. DUPLICATION OR TRANSMITTAL OF THIS DOCUMENT IS STRICTLY PROHIBITED WITHOUT THE WRITTEN CONSENT OF CANADIANPOND.CA PRODUCTS LTD.



	DESSINÉ PAR / DRAWN BY:	NOM / NAME:	DATE:
	APPROUVÉ PAR / APPROVED BY:	D. MARTIN	03-07-2017
		M. PARIS	
513 KNOWLTON ROAD, KNOWLTON, QUÉBEC, JOE 1W0, TEL: 450-243-0976, FAX: 450-243-1834			

TITRE / TITLE:

Tuyau® Bulle®
Bub Bubble® Tubing® ing®