

Rocking Piston Compressors

- Oil-less motor
- 120V or 230V (60 Hz or 50Hz)
- Continuous or intermittent duty
- UL, CSA & CE approved
- 6' power cord
- Low-level of noise (65 dB)
- 3-years limited warranty
(Piston cylinders: 2-years)
- Thermal overload protection
- Ramped internal valve plate allows for a restart under load after power failures.

Sold with:

- 40 PSI pressure relief valve
- Intake air filter assembly



CSP14.50



CDP12.50



CDP34.50



MODEL	CSP14.50		CDP12.50		CDP34.50	
HP / 60 Hz	1/4		1/2		3/4	
Volt / Hz	115	230	115	230	115	230
Amp @ 0 PSI	2.2	1.1	3.0	1.5	5.4	3.1
Amp @ 20 PSI	3.2	1.6	4.0	2.0	6.9	3.7
Dimension (in)	7.1 x 6.3 x 7.8		9.4 x 6.3 x 7.8		10.8 x 6.5 x 9.5	
Weight (lb)	16		19		28	
Air flow at PSI	CFM		CFM		CFM	
0	3.8		5.5		7.4	
5	3.4		4.9		7.2	
10	3.2		4.8		6.8	
15	3.1		4.5		6.7	
20	2.9		4.2		6.4	
25	2.7		4.0		6.2	
30	2.6		3.6		6.0	
40	2.4		3.2		5.6	
50	2.2		2.7		5.0	

*Actual results may vary based on power and environmental conditions.